

Variable Messaging Trailer



King Highway Products Ltd

Riverside, Market Harborough, Leicestershire, LE16 7PX

Tel: 01858 467361 Fax: 01858 467161 email: sales@traiload.co.uk Web: www.traiload.co.uk

The company pursues a policy of continuous product development and reserves the right to make any changes to these specifications it considers necessary.



- LED matrix board is capable of displaying any static or dynamic Variable Message Signs (VMS), text or symbols
- Matrix board is available with red, amber, white and blue LEDs
- Highly legible signs even in bright daylight
- Available as partially or fully populated versions
- Simple handset control of matrix board
- Optional remote control and monitoring
- All signs stored on a "memory stick" which can easily be re-programmed
- Remote activation and sign creation available as an option



Technical Data

Housing:	aluminium, water reistant seal (ALMG3), black powder coated.
Weight:	approx. 145 kgs
Size of housing:	2,190 x 1,590 x 130 mm
Size of LED area:	1,680 x 1,200 mm
LED / m ² Matrix:	4,444
No. of LEDs:	8,960 per colour
Light source:	15°, LED red, amber, white 5 mm
LED pitch:	15 mm
Matrix brightness:	amber / red: 20,000 cd / m ² white: 18,200 cd / m ²
Voltage:	12 / 24 V nominal
Auto brightness adaption:	continuos 5% - 100%, also manually adjustable
Data storage:	250 sybnols per memory stick

