

WUMAG PALFINGER**RANGE DETAILS**

Model	Working Height (m)	Maximum Outreach (m)	Platform Capacity	Minimum Vehicle GVW (Kg)	Turret Rotation
WTB 220	22.00	14.00	200	3,500	460
WGT 250	25.00	16.90	265	14,000	460
WDT 110	11.00	6.80	200	3,500	460
WDT 125	12.50	7.50	200	3,500	480
WDT 140	14.00	9.20	200	5,000	540
WT 170	17.00	11.80	250	7,500	540
WT 230	22.75	17.50	350	7,500	540
WT 270	27.00	20.00	350	7,500	540
WT 300.3	30.00	19.00	320	7,500	500
WT 350.3	35.00	30.00	300	14,000	540
WT 370	37.00	29.50	700	18,000	540
WT 450	45.00	30.00	700	18,000	540
WT 530	53.00	40.00	700	26,000	540
WT 610	61.00	37.00	700	32,000	540
WT 700	70.00	35.00	700	33,000	540
WT 1000	102.50	36.00	600	60,000	Endless

King Highway Products Ltd

Riverside, Market Harborough, Leicestershire, LE16 7PX

Tel: 01858 467361 Fax: 01858 467161 email: sales@skyking.co.uk Web: www.skyking.co.uk

The company pursues a policy of continuous product development and reserves the right to make any changes to these specifications it considers necessary.